



Technical  
**Datasheet**  
2023 v1



Movexx

# TT1000-T-Cleanroom

» move your work **easier**

# TECHNICAL DATA TT1000-T-Cleanroom

According to VDI 2198

<b>Characteristics</b>	<b>1.1</b>	Manufacturer		Movexx International B.V.
	<b>1.2</b>	Model designation		TT1000-T-Cleanroom
	<b>1.3</b>	Power unit		Electric w. AGM-VRLA battery
	<b>1.4</b>	Operation type		Tilting
	<b>1.5*</b>	Rated capacity/Load capacity	Q [t]	1
	<b>1.7**</b>	Rated drawbar pull	F [N]	345
<b>Wt</b>	<b>1.9</b>	Wheelbase	y [mm]	-
	<b>2.1</b>	Weight, incl battery	kg	43
<b>Wheels types</b>	<b>2.2</b>	Axle load without load	front/rear	kg
	<b>3.1</b>	Tyres		Solid rubber/non-marking/CR
	<b>3.2</b>	Tyre size	front	mm
	<b>3.3</b>	Tyre size,	rear	mm
	<b>3.4</b>	Auxiliary wheel size		mm
	<b>3.5</b>	Wheels, number front/rear (x = drive)		-/x2
<b>Dimensions</b>	<b>3.6</b>	Tread width	front/rear	b <sub>10</sub> /b <sub>11</sub> [mm]
	<b>4.9</b>	Tiller height	min./max.	h <sub>14</sub> [mm]
	<b>4.12</b>	Tow coupling height		h <sub>10</sub> [mm]
	<b>4.19</b>	Total length		l <sub>1</sub> [mm]
	<b>4.21</b>	Total width		b <sub>1</sub> [mm]
	<b>4.32</b>	Ground clearance, center of wheel base		m <sub>2</sub> [mm]
<b>Performance</b>	<b>4.35</b>	Turning radius		W <sub>a</sub> [mm]
	<b>5.1</b>	Travel speed forwards	with/without load	km/h
	<b>5.1.1</b>	Travel speed backwards	with/without load	km/h
	<b>5.5**</b>	Max. drawbar pull (S2 = 60 Min)	with/without load	N
	<b>5.6**</b>	Max. drawbar pull (S2 = 5 Min)	with/without load	N
	<b>5.8*</b>	Maximum slope (5 min)	with/without load	%
<b>Drive</b>	<b>5.9</b>	Acceleration	with/without load	s
	<b>5.10</b>	Service brake		-
<b>Other</b>	<b>6.1</b>	Drive motor output (S2 = 60 Min)	kW	0,3
	<b>6.4</b>	Battery voltage, nominal capacit	[V/Ah]	24/22
<b>Other</b>	<b>8.1</b>	Drive control		DC
	<b>10.7</b>	Noise level	dB(A)	65

\* The maximum payload is affected by the type of slope, operating time and floor type.

\*\* The maximum drawbar load on the hook [N] is determined by the engine power of the machine but is affected by the type of wheels of the machine and of the towed trolley/load, the type of surface and the driveable weight of the machine.

